MILA DS-A007

With Mila series we opted for a simple cylindrical shape that can host the dynamic range of features and options our client believe are essential in a suspended mount downlight. With illumination levels and beam angles for every application and colour rendering to bring out the best in your design, we present Mila as an ideal option for your suspended downlight design.

Other options include CCT colour and a glass diffuser.
Phase dimmable with 0-10V available on request.



PRODUCT FEATURES

- Light output, up to 3,300Lm
- • Efficacy (up to 115Lm/W) delivering superior energy efficiency
- • Ideal for all commercial applications
- • Life time 50,000 hours at 70% lumen maintenance
- • Colour rendering exceeds CRI:80/90
- • Beam Angle: 10°/25°/45°/53°
- • CCT options 3000K/4000K/5000K
- • Available in Surface and Suspended
- • Available colours black and white
- • Dimming options on request
- • Direct connection
- • Five Year Warranty

IP 20 | CRI >80 | CRI >90 | FIVE YEARS 5 WARRANTY

Dimensions Ø117x175mm

Model	Lumen Output	System Power	CCT	Beam Angle
DS-A007-J	2300Lm	20W	3000K/4000K	10°/25°/45°/53°
DS-A007-K	3300Lm	30W	3000K/4000K	10°/25°/45°/53°
CRI	**Material**	**Voltage**	**Colour**	**Dimming Options**
>80/>90	Aluminium	230V 50Hz	BK / WH	Available on request

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.