



## Firefly | 2 W | 360° | Bollards


700 mm mounting by housing box

Cod: FI30070XHB7ZL



### Technical Specifications


Source lamp	LED 2 W
Total wattage	2
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	119 lm (160 lm*) @ 3000 K
Luminous efficacy	59.5 lm/W @ 3000 K
McADAM steps	3
Beam	360°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	65
IK rating	8
Insulation class	III




### Materials

Body	Extruded aluminium EN AW6026
Diffuser	Opal PMMA
Finishing	Graphite - Polyester powder paint

## Isolux



## Photometry



## Included accessories

- 0.5 m length cable -05RN-F
- Housing box

## Available accessories

<b>0404M011</b>	Single connection IP68
<b>0409BT016</b>	Transformer _ 24 Vdc - 100 W Connect up to 30 device
<b>0409BT014</b>	Transformer _ 24 Vdc - 12 W Connect up to 4 device
<b>0409BT015</b>	Transformer _ 24 Vdc - 25 W Connect up to 8 device

For office locations visit [www.lpalighting.com](http://www.lpalighting.com)