



Kuboid 120 | 13 W | flood 45° | Projectors

Cod: KB60PROFHB10G




Technical Specifications

| | |
|------------------------------|--|
| Source lamp | LED 13 W |
| Total wattage | 16 |
| Voltage | 220-240 Vac - 50/60 Hz |
| Control | On/Off • dimmable on request |
| Luminous flux (*Source flux) | 1307 lm (1530 lm*) @ 3000 K |
| Luminous efficacy | 81.7 lm/W @ 3000 K |
| McADAM steps | 3 |
| Beam | flood 45° |
| CRI | >90 |
| Life time | L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C |
| Energy efficiency class | A++ |
| IP rating | 67 |
| IK rating | 8 |
| Insulation class | I |

90°



12



Materials


| | |
|-----------|--------------------------------|
| Body | Die-cast aluminium EN47100 |
| Diffuser | Serigraphed transparent glass |
| Finishing | Black - Polyester powder paint |

For office locations visit www.lpalighting.com

E (lux)

Photometry

| H (m) | lux (3000 K) | Ø (m) |
|-------|--------------|-------|
| 1.00 | 2056 | 0.82 |
| 2.00 | 514 | 1.64 |
| 3.00 | 228 | 2.46 |
| 4.00 | 128 | 3.28 |
| 5.00 | 82 | 4.10 |



Available accessories

0404M010

Single connection IP68

00AKB60-80

Steel fixing kit - spike

For office locations visit www.lpalighting.com