




Lyras 130 | 20 W | double spot 18° / wide flood 60° | Wall lamps

Cod: LY70PAR6HB10M

Technical Specifications



Source lamp	LED 20 W
Total wattage	25
Voltage	220-240 Vac - 50/60 Hz
Control	On/Off • dimmable on request
Luminous flux (*Source flux)	2288 lm (2600 lm*) @ 3000 K
Luminous efficacy	91.5 lm/W @ 3000 K
McADAM steps	3
Beam	double spot 18° / wide flood 60°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	I



Materials

Body	Die-cast aluminium EN47100
Diffuser	Extra clear tempered glass 13 mm
Finishing	Light grey - Polyester powder paint

For office locations visit www.lpalighting.com

E (lux)

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	8850/1054	8850/1054	0.3/1.2
2.00	2212/264	2212/264	0.6/2.3
3.00	983/117	983/117	0.9/3.5
4.00	553/66	553/66	1.2/4.7
5.00	354/42	354/42	1.6/5.9

Photometry

