



## Wall Mira 45 | 2 W | diffuse 80° | Wall recessed

Also available for floor recessed


Cod: MI20IPADHB7Z1

## Technical Specifications

all the technical specifications are related to one head only



Source lamp	LED 2 W
Total wattage	2
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	17 lm (160 lm*) @ 3000 K
Luminous efficacy	8.5 lm/W @ 3000 K
McADAM steps	3
Beam	diffuse 80°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	III




## Materials

Body	Extruded aluminium EN AW6060
Diffuser	Frosted tempered glass 6 mm
Finishing	Inox - Anodized

E (lux)

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	12	12	1.65
2.00	3	3	3.3
3.00	1	1	4.95
4.00	1	1	6.6
5.00	0	0	8.25

## Photometry



## Included accessories

- 1 m length cable -05RN-F
- Housing box

## Available accessories

<b>0409BT016</b>	Transformer _ 24 Vdc - 100 W Connect up to 30 devices
<b>0409BT014</b>	Transformer _ 24 Vdc - 12 W Connect up to 4 devices
<b>0409BT015</b>	Transformer _ 24 Vdc - 25 W Connect up to 8 devices

For office locations visit [www.lpalighting.com](http://www.lpalighting.com)