



Wall Mira 65 | 5 W | diffuse 90° | Wall recessed



Also available for floor recessed

Cod: MI30IPADHB7Z2

Technical Specifications



Source lamp	LED 5 W
Total wattage	5
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	88 lm (480 lm*) @ 3000 K
Luminous efficacy	17.6 lm/W @ 3000 K
McADAM steps	3
Beam	diffuse 90°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	III




Materials

Body	Extruded aluminium EN AW6060
Diffuser	Frosted tempered glass 8 mm
Finishing	Bronze - Anodized

E (lux)

Photometry

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	48	48	1.94
2.00	12	12	3.88
3.00	5	5	5.82
4.00	3	3	7.76
5.00	2	2	9.7



Included accessories

- 1 m length cable -05RN-F
- Housing box

Available accessories

0404M009	Single connection IP68
0409BT016	Transformer _ 24 Vdc - 100 W Connect up to 12 devices
0409BT014	Transformer _ 24 Vdc - 12 W Connect up to 1 device
0409BT015	Transformer _ 24 Vdc - 25 W Connect up to 3 devices

For office locations visit www.lpalighting.com