


## **LEGEND SR-A576**

The Legend series is a versatile professional downlight for all commercial applications. The Legend is adjustable with a 355° rotation providing the additional advantage for an exact and accurate aiming of the product on space.

Energy efficiency is a key component of our product focus and the Legend series are at the top of the performance scale, ensuring significant energy savings over many alternative solutions. Phase dimmable with 0-10V and DALI available upon request.





| Model     | Source Power (W) | System Power (W) | Source Lumen (Lm)<br>(CRI>80, 3000K) | System Lumen (Lm) / Beam Angle<br>(CRI>80, 3000K) |                             |                                    |                           |
|-----------|------------------|------------------|--------------------------------------|---|-----------------------------|------------------------------------|---------------------------|
|           |                  |                  |                                      | Very Narrow<br>(10°/11°/11°/23°)                  | Narrow<br>(24°/24°/24°/23°) | <b>Medium</b><br>(42°/43°/43°/44°) | Wide<br>(64°/63°/64°/59°) |
| SR-A576-J | 17               | 20               | 2280                                 | 2077  | 2052                        | 2049                               | 2034                      |
| SR-A576-K | 25               | 30               | 3260                                 | 3094  | 3079                        | 3026                               | 3001                      |
| SR-A576-L | 32               | 37               | 3850                                 | 3694  | 3702                        | 3643                               | 3634                      |
| SR-A576-M | 36               | 42               | 4640                                 | 4337  | 4233                        | 4290                               | 4360                      |

| CRI     | ССТ         | Material  | LED Lifetime     | Colour  | Voltage   | Dimming              |
|---------|-------------|-----------|------------------|---------|-----------|----------------------|
| >80/>90 | 3000K/4000K | Aluminium | 50,000 hrs (L70) | BK / WH | 230V 50Hz | Available on request |



For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.

## Accessories

(available on request)






Cross Accessory


Glass Lens


Honeycomb Lens

## Photometrics

(standard beam angles, alternative available on request)









For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.