



Wall Mira 45 | 2 W | 360° | Wall recessed

Cod: MI20IPAXNB7Z1


Also available for floor recessed



## Technical Specifications

all the technical specifications are related to one head only

Source lamp	LED 2 W
Total wattage	2
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	20 lm (160 lm*) @ 4000 K
Luminous efficacy	10 lm/W @ 4000 K
McADAM steps	3
Beam	360°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	III




## Materials

Body	Extruded aluminium EN AW6060
Diffuser	Opal polycarbonate
Finishing	Inox - Anodized

E (lux)

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	4	4	7.9
2.00	1	1	15.8
3.00	0	0	23.7
4.00	0	0	31.6
5.00	0	0	39.5

## Photometry



## Included accessories

- 1 m length cable -05RN-F
- Housing box

## Available accessories

<b>0409BT016</b>	Transformer _ 24 Vdc - 100 W Connect up to 30 devices
<b>0409BT014</b>	Transformer _ 24 Vdc - 12 W Connect up to 8 devices
<b>0409BT015</b>	Transformer _ 24 Vdc - 25 W Connect up to 4 devices

For office locations visit [www.lpalighting.com](http://www.lpalighting.com)