



Wall Mira 65 | 5 W | 120° | Wall recessed


Cod: MI30IPAVHB7Z1

Also available for floor recessed



## Technical Specifications


Source lamp	LED 5 W
Total wattage	5
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	26 lm (480 lm*) @ 3000 K
Luminous efficacy	5.2 lm/W @ 3000 K
McADAM steps	3
Beam	120°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	III




## Materials

Body	Extruded aluminium EN AW6060
Diffuser	Opal polycarbonate
Finishing	Inox - Anodized

## Isolux



## Photometry



## Included accessories

- 1 m length cable -05RN-F
- Housing box

## Available accessories

<b>0404M009</b>	Single connection IP68
<b>0409BT016</b>	Transformer _ 24 Vdc - 100 W Connect up to 12 devices
<b>0409BT014</b>	Transformer _ 24 Vdc - 12 W Connect up to 1 device
<b>0409BT015</b>	Transformer _ 24 Vdc - 25 W Connect up to 3 devices

For office locations visit [www.lpalighting.com](http://www.lpalighting.com)