



Wall Mira 65 | 5 W | 360° | Wall recessed



Cod: MI30IPAXNB7Z1

Also available for floor recessed



Technical Specifications

Source lamp	LED 5 W
Total wattage	5
Voltage	24 Vdc
Control	Power supply not included • dimmable on request
Luminous flux (*Source flux)	95 lm (480 lm*) @ 4000 K
Luminous efficacy	19 lm/W @ 4000 K
McADAM steps	3
Beam	360°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
Energy efficiency class	A++
IP rating	66
IK rating	8
Insulation class	III



Materials


Body	Extruded aluminium EN AW6060
Diffuser	Opal polycarbonate
Finishing	Inox - Anodized

For office locations visit www.lpalighting.com

E (lux)

Photometry

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	20	20	7.3
2.00	5	5	14.6
3.00	2	2	21.9
4.00	1	1	29.3
5.00	1	1	36.6



Included accessories

- 1 m length cable -05RN-F
- Housing box

Available accessories

0404M009	Single connection IP68
0409BT016	Transformer _ 24 Vdc - 100 W Connect up to 12 devices
0409BT014	Transformer _ 24 Vdc - 12 W Connect up to 1 device
0409BT015	Transformer _ 24 Vdc - 25 W Connect up to 3 devices

For office locations visit www.lpalighting.com