

INDUS II PANEL (COI)

LED panels revolutionised lighting in commercial and retail spaces and our market-leading products and options are ready to meet your every application. Our quality reflects our focus on flexibility; a flexibility that ensures the best lighting outcome for every client. The ultra slim profile fits seamlessly into any workplace and can be T-bar, plaster recessed, surface mounted or suspended. The micro-prismatic diffuser delivers low-glare and our LED selection ensures excellent colour rendering to further enhance the comfort and efficiency of the lit space.

Applications: Offices, educational, retail stores, supermarkets, hospitals, health services etc.



PRODUCT FEATURES

- Light output: Up to 1,800Lm
- Efficacy: Up to 100Lm/W
- Ideal for all applications
- Life time: 50,000 hours (L70)
- Colour rendering exceeds CRI:90
- Cyanosis Observation Index <3.0
- Beam Angle: 90°
- CCT options: 3000K/4000K
- UGR<19
- Sizes to fit standard TBar ceilings
- Plaster and surface mount frame accessories available
- Suspension kit available
- Available colour: white
- Dimming options on request
- Flex and plug or direct connection
- VSBA Building Quality Standard 2019
- Five Year Warranty

















Model	Delivered Lumens	System Power	CCT	Beam Angle
PA-INDR2-18	1800Lm	18W	3000K/4000K	90°
CRI	Material	Voltage	Colour	Dimming Options
>90	Aluminium	220-240V, 50Hz	White	Available on request



Accessories

(available on request)









Plaster Frame

Surface Mount Frame

Semi Flush Frame

Shallow Surface Mount Frame



Suspension Kit

Photometrics

(standard beam angles, alternative available on request)





