



SURFACE PROFILE (FLS-2835-SM1715)

With its aluminium finish, this surface high profile is an ideal choice to protect LED strip lighting and perform as a heat sink to maintain the longevity of the fitting. It offers several configurations with different LED strips and is available with a PMMA opal, frosted, clear or black diffuser cover. This profile is suitable for a variety of applications such as shelving, accent lighting, joineries, furniture and under cabinets.




End cap



Mounting clip



Adjustable clip



PRODUCT FEATURES

- Light output: Up to 1,760Lm/M
- Efficacy: Up to 135Lm/W
- Ideal for all applications
- Life time: L70 (9K) >54,000 hours
- Colour rendering exceeds CRI:>80/>90
- Beam Angle 120° viewing angle
- Diffuser: PMMA opal, frosted, clear or black
- Installation: Surface
- Accessories: End caps, mounting clip, adjustable clip
- CCT options 2800~6500K
- Dimming options on request
- Flex and plug or direct connection
- Five Year Warranty



Model	Delivered Lumens	System Power	CCT	LEDs/M	LED Width
LPA-FLS-2835-SM1715-5	656Lm/M	4.8W/M	3000K/4000K	64 LEDs/M	8x1.2mm
LPA-FLS-2835-SM1715-10	1330Lm/M	9.6W/M	3000K/4000K	128 LEDs/M	8x1.2mm
LPA-FLS-2835-SM1715-13	1760Lm/M	13W/M	3000K/4000K	160 LEDs/M	8x1.2mm

Beam Angle	CRI	Material	Voltage	Colour	Dimming Options
120°	>80/>90	Aluminium	24V DC	BK / WH / SIL	Available on request

* Values are based on LED Strip