

SURFACE PROFILE (FLS-2835-AS5032A)

With its aluminium finish, this surface profile is an ideal choice to protect LED strip lighting and perform as a heat sink to maintain the longevity of the fitting. It offers several configurations with different LED strips and is available with a PMMA frosted or black diffuser cover. This profile is suitable for a variety of applications such as shelving, accent lighting, joineries, furniture and under cabinets.




End cap



Mounting clip



Suspension kit



PRODUCT FEATURES

- Light output: Up to 3,520Lm/M
- Efficacy: Up to 138Lm/W
- Ideal for all applications
- Life time: L70 (9K) >54,000 hours
- Colour rendering exceeds CRI:>80/>90
- Beam Angle 120° viewing angle
- Ideal for all applications
- Installation: Surface
- Diffuser: PMMA Frosted/Black
- Accessories: End caps, clips, 2m suspension kit
- CCT options 2800~6500K
- Available colours: black, white and silver
- Five Year Warranty



Model	Delivered Lumens	System Power	CCT	LEDs/M	LED Width
LPA-FLS-2835-AS5032A-10	2x656Lm/M	2x4.8W/M	3000K/4000K	64 LEDs/M	8x1.2mm
LPA-FLS-2835-AS5032A-20	2x1330Lm/M	2x9.6W/M	3000K/4000K	128 LEDs/M	8x1.2mm
LPA-FLS-2835-AS5032A-26	2x1760Lm/M	2x13W/M	3000K/4000K	160 LEDs/M	8x1.2mm

Beam Angle	CRI	Material	Voltage	Colour	Dimming Options
120°	>80/>90	Aluminium	24V DC	BK / WH / SIL	Available on request

* Values are based on LED Strip