





Kuboid 45 | 1.5 W | medium 33° | Projectors Cod: KB30PROMHB7ZG



Technical Specifications

Source lamp	LED 1.5 W
Total wattage	1.5
Voltage	24 Vdc
Control	On/Off
Luminous flux (*Source flux)	98 lm (137 lm*) @ 3000 K
Luminous efficacy	65 lm/W @ 3000 K
McADAM steps	3
Beam	medium 33°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
IP rating	65
IK rating	6
Insulation class	III



Materials

Body	Die-cast aluminium EN47100
Diffuser	Serigraphed transparent glass
Finishing	Black - Polyester powder paint


For office locations visit www.lpalighting.com



E (lux)

H(m)	lux(3000 K)	Ø(m)
1.00	180	1.04
2.00	45	1.3
3.00	20	2.30
4.00	11	2.54
5.00	7	3.18

Photometry



Included accessories

- 1 m length cable -05RN-F

Available accessories

0404M009	Single connection IP68
00AKB30_	Steel fixing kit - spike
0409BT016	Transformer _ 24 Vdc - 100 W Connect up to 30 pcs
0409BT014	Transformer _ 24 Vdc - 12 W Connect up to 4 pcs
0409BT015	Transformer _ 24 Vdc - 25 W Connect up to 8 pcs