





Kuboid 45 | 1.5 W | spot 12° | Projectors

Cod: KB30PROSHB7ZG



## Technical Specifications

Source lamp	LED 1.5 W
Total wattage	1.5
Voltage	24 Vdc
Control	On/Off
Luminous flux (*Source flux)	108.5 lm (137 lm*) @ 3000 K
Luminous efficacy	72 lm/W @ 3000 K
McADAM steps	3
Beam	spot 12°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
IP rating	65
IK rating	6
Insulation class	III



## Materials

Body	Die-cast aluminium EN47100
Diffuser	Serigraphed transparent glass
Finishing	Black - Polyester powder paint


For office locations visit [www.lpalighting.com](http://www.lpalighting.com)



E (lux)

H(m)	lux (3000 K)	Ø(m)
1.00	844	0.22
2.00	211	0.44
3.00	94	1.04
4.00	53	1.26
5.00	34	1.07

Photometry



## Included accessories

-	1 m length cable -05RN-F
---	--------------------------

## Available accessories

0404M009	Single connection IP68
00AKB30_	Steel fixing kit - spike
0409BT016	Transformer _ 24 Vdc - 100 W Connect up to 30 pcs
0409BT014	Transformer _ 24 Vdc - 12 W Connect up to 4 pcs
0409BT015	Transformer _ 24 Vdc - 25 W Connect up to 8 pcs