





Kuboid 45 | 1.5 W | diffuse | Projectors

Cod: KB31PRODHB7ZG



Technical Specifications

| | |
|------------------------------|----------------------------------------------------|
| Source lamp | LED 1.5 W |
| Total wattage | 1.5 |
| Voltage | 24 Vdc |
| Control | On/Off |
| Luminous flux (*Source flux) | 19 lm (137 lm*) @ 3000 K |
| Luminous efficacy | 12 lm/W @ 3000 K |
| McADAM steps | 3 |
| Beam | diffuse |
| CRI | >90 |
| Life time | L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C |
| IP rating | 65 |
| IK rating | 6 |
| Insulation class | III |



Materials

| | |
|-----------|--------------------------------|
| Body | Die-cast aluminium EN47100 |
| Diffuser | Serigraphed opal glass |
| Finishing | Black - Polyester powder paint |


For office locations visit www.lpalighting.com



E (lux)

| H(m) | lux (3000 K) | Ø(m) |
|------|--------------|-------|
| 1.00 | 16 | 2.10 |
| 2.00 | 4 | 4.20 |
| 3.00 | 2 | 6.30 |
| 4.00 | 1.2 | 8.36 |
| 5.00 | 1 | 10.45 |

Photometry



Included accessories

- 1 m length cable -05RN-F

Available accessories

| | |
|-----------|------------------------------------------------------|
| 0404M009 | Single connection IP68 |
| 00AKB30_ | Steel fixing kit - spike |
| 0409BT016 | Transformer _ 24 Vdc - 100 W Connect up to 30 pcs |
| 0409BT014 | Transformer _ 24 Vdc - 12 W Connect up to 4 pcs |
| 0409BT015 | Transformer _ 24 Vdc - 25 W Connect up to 8 pcs |