





## Kuboid 45 | 1.5 W | wide flood 65° | Projectors

## Technical Specifications

Cod: KB30PROWHB7ZG



Source lamp	LED 1.5 W
Total wattage	1.5
Voltage	24 Vdc
Control	On/Off
Luminous flux (*Source flux)	191 lm (137 lm*) @ 3000 K
Luminous efficacy	68 lm/W @ 3000 K
McADAM steps	3
Beam	wide flood 65°
CRI	>90
Life time	L 70 > 50.000 h Ta 25°C L 70 > 50.000 h Ta 40°C
IP rating	65
IK rating	6
Insulation class	III



## Materials

Body	Die-cast aluminium EN47100
Diffuser	Serigraphed transparent glass
Finishing	Black - Polyester powder paint






E (lux)

H(m)	lux (3000 K)	Ø(m)
1.00	104	1.07
2.00	26	2.14
3.00	12	3.21
4.00	6	4.28
5.00	4	5.35

Photometry



Included accessories

- 1 m length cable -05RN-F

Available accessories

0404M009	Single connection IP68
00AKB30_	Steel fixing kit - spike
0409BT016	Transformer _ 24 Vdc - 100 W Connect up to 30 pcs
0409BT014	Transformer _ 24 Vdc - 12 W Connect up to 4 pcs
0409BT015	Transformer _ 24 Vdc - 25 W Connect up to 8 pcs