




## LED STRIP

Flexible strip lighting is an effective and economic way to highlight architectural elements or illuminate other areas to particular affect. Our commercial grade strip offers four illumination levels and two CCT colours. The five metre lengths can be cut to fit (by a suitably qualified person) or used in multiples length combinations.


### Please note:

- Power supplies must be ordered separately to meet the particular design. Please contact your local LPA office for assistance.
- Flexible LED Strip must always be used in a suitable enclosure for heat management and mechanical protection. Please see our range of General Purpose and Weatherproof Enclosures.


5W



10W / 13W



23W



### PRODUCT FEATURES

- Light output: Up to 3670Lm/M
- Efficacy: Up to 158Lm/W
- Ideal for all commercial applications
- Life time: L70 (9K) >54,000 hours
- Colour rendering exceeds CRI:>80/>90
- Beam Angle 120° viewing angle
- CCT options 2800~6500K
- IP20, IP65 (silicon glue), IP66 (silicon sleeve), are optional
- Operating Temperature (Ta) -20C ~ + 45C
- Dimming options on request
- Flex and plug or direct connection
- Five Year Warranty



Model	Delivered Lumens	System Power	CCT	LEDs/M	LED Width
LPA-FLS-2835-5	656Lm/M	4.8W/M	3000K/4000K	64 LEDs/M	8x1.2mm
LPA-FLS-2835-10	1330Lm/M	9.6W/M	3000K/4000K	128 LEDs/M	8x1.2mm
LPA-FLS-2835-13	1760Lm/M	13W/M	3000K/4000K	160 LEDs/M	8x1.2mm
LPA-FLS-2835-23	3670Lm/M	23W/M	3000K/4000K	128 LEDs/M	12x1.2mm

Beam Angle	CRI	Material	Voltage	Colour	Dimming Options
120°	>80/>90	Aluminium	24V DC	BK / WH / SIL	Available on request