


## HALO DOWNLIGHT (6")

The Halo is an excellent choice as a low glare entry level downlight for commercial and retail applications with a shallow depth to suit low ceiling spaces. Its adjustable CCT switch provides a variation of colour temperatures to accommodate your lighting requirements.

**Applications:** offices, supermarkets, hotels, restaurants, retail stores, wet areas and more.



## **PRODUCT FEATURES**

- Light output: Up to 2,830Lm
- Efficacy: Up to 94Lm/W
- · Ideal for all commercial and residential applications
- LED Lifetime (L70B50): >60,000 hours
- Colour rendering exceeds CRI>80
- Beam Angle: 90°
- Ultra Low Glare Diffuser
- Protection rating IP44
- CCT adjustable switch
- CCT options: 3000K/4000K/5700K
- Available colour: white
- Dimming: Dali on request
- Five Year Warranty



Model	Delivered Lumens	System Power	CCT Switchable	Beam Angle
DR-HAL6-25	2148Lm	25W	3000K-4000K-5700K	90°
DR-HAL6-35	2570-2830Lm	35W	3000K-4000K-5700K	90°
CRI	Material	Voltage	Colour	<b>Dimming Options</b>
>80	Aluminium	220-240V, 50Hz	White	Available on request




For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.

## Photometrics

(standard beam angles, alternative available on request)





For office locations visit <u>www.lpalighting.com</u>

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.