
VISI DR-A578

Visi is an everyday downlight made for professional applications. Once recessed into the ceiling the Visi blends in effortlessly with its narrow trim and provides an anti-glare comfort light. However, trim size is no reflection on performance and Visi provides a full range of illumination levels in both fixed and adjustable design.

Energy efficiency is key and the Visi series are at the top of the performance scale, ensuring significant energy savings over alternative solutions. CCT colours, a honeycomb louvre and dimming options are available on request.





	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
Model				Narrow (12°/12° /12°/13°)	Narrow (20°)	Medium (43°)	Wide (59°)
DR-A578-J	17	19	2269	2231	2175	2151	2178
DR-A578-K	25	27	3107	2995	2885	2862	2885
DR-A578-L	32	35	3985	3701	3630	3591	3631
DR-A578-M	36	39	4454	4334	4171	4204	4212

CRI	ССТ	Material	LED Lifetime	Colour	Voltage	Dimming
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request



For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.



Accessories

(available on request)








Honeycomb Louvre


Elliptical Lens





Photometrics

(standard beam angles, alternative available on request)











For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.