



## NANI SR-A921

The Nani series is a fully adjustable downlight. With up to 70° tilt and 355° rotation, this downlight proves an excellent option for wide beam spread and wall washing in retail and commercial spaces.

Energy efficiency is a key component of our product focus and options for CCT colours and accessories are available.




Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				Narrow (13°/13°/13°/14°)	Narrow (20°/20°/20°/21°)	Medium (43°/43°/43°/44°)	Wide (60°/59°/61°/60°)
SR-A921-J	17	19	2269	2259	2184	2145	2079
SR-A921-K	25	27	3107	3013	2945	2907	2809
SR-A921-L	32	35	3985	3797	3678	3667	3302
SR-A921-M	36	39	4454	4332	4265	4194	4088

CRI	CCT	Material	LED Lifetime	Colour	Voltage	Dimming
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request

## Accessories

(available on request)



Honeycomb Louvre



Elliptical Lens



Glass Lens

## Photometrics

(standard beam angles, alternative available on request)

