

VISI SR-A931

Visi is an everyday downlight made for professional applications. Once recessed into the ceiling the Visi blends in effortlessly with its narrow trim and provides an anti-glare comfort light. However, trim size is no reflection on performance and Visi provides a full range of illumination levels in both fixed and adjustable design.

Energy efficiency is key and the Visi series are at the top of the performance scale, ensuring significant energy savings over alternative solutions. CCT colours, a honeycomb louvre and dimming options are available on request.



Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				Narrow (18°/19°)	Medium (26°)	Medium (40°)	Wide (53°/49°)
SR-A931-A	7	8	872	698	754	741	734
SR-A931-B	12	14	1439	1168	1260	1239	1222
CRI	ССТ	Material	LED Lifetime	Colour	Voltage	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request	



For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.



Accessories


(available on request)





Honeycomb Louvre


Photometrics

(standard beam angles, alternative available on request)











For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.