

## NANI SR-C028

The Nani series is a fully adjustable downlight. With up to 70° tilt and 355° rotation, this downlight proves an excellent option for wide beam spread and wall washing in retail and commercial spaces.

Energy efficiency is a key component of our product focus and options for CCT colours and accessories are available.





Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				<b>Narrow</b> (15°/15°/16°)	Narrow (19°)	<b>Medium</b> (42°/41°/41°)	<b>Wide</b> (58°)
SR-C028-J	17	19	2269	2204	2201	2167	2065
SR-C028-K	25	27	3107	2953	2951	2896	2783
SR-C028-L	32	35	3985	3689	3721	3609	3456
CRI	ССТ	Material	LED Lifetime	Colour	Voltage	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request	



For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.

## Accessories

(available on request)








Honeycomb Lens


Elliptical Lens





## **Photometrics**

(standard beam angles, alternative available on request)









For office locations visit www.lpalighting.com

LIGHTING AND ENERGY SOLUTIONS

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.