


CARL ST-C615

The Carl series offers a sleek range of LED track lights ideal for retail, hospitality and general display applications. Carl offers a versatile range of light head designs, illumination levels and beam angles. With our market-leading colour rendering and easy adjustability, we confidently recommend Carl as an ideal luminaire to bring out the best in your design.

All fixtures fit a standard three-circuit track and adjust through 90° vertical plane and 355° horizontal plane. Options include CCT colour, onboard or on-track driver, glass, elliptical lens and honeycomb diffusers, and barn door cut-off control.

Available in surface mount and suspended format.





Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				Narrow (14°)	Narrow (22°)	Medium (36°)	Wide (58°)
ST-C615-J	17	19	2269	2074	2014	2034	1977
ST-C615-K	25	27	3107	2866	2744	2776	2685
CRI	CCT	Material	LED Lifetime	Colour	Voltage	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on reques	



Accessories

(available on request)









Honeycomb Louvre

Elliptical Lens

Barn Door Louvre


Glass Lens




Surface Mounted Canopy

Photometrics

(standard beam angles, alternative available on request)





O AVERAGE BEAM ANGLE (50%):35.5 DEG C90/270,35.2

