


## **GRACE DR-A382**

Grace adopts an innovative all-in-one design integrating the heatsink and outer trim. It effectively expands the heat dissipation area and improves the lifetime of the light fixtures. Equipped with lenses as optical accessories and offering a variety of front reflector colours, the Grace series effectively minimises glare. Available in fixed, adjustable and surfacemounted versions to suit your specific needs.





















Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				Narrow (16°/21°/21°)	Narrow (18°/23°/23°)	<b>Medium</b> (32°/34°/35°)	Wide (57°/56°/56°)
DR-A382-A	7	8	872	696	728	725	746
DR-A382-B	12	14	1586	1381	1460	1455	1480
DR-A382-J	17	19	2120	1854	1955	1950	1980
CRI	CCT	Material	LED Lifetime	Colour	Voltage	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request	



## **Accessories**

(available on request)

## Reflectors available in different colours



## **Photometrics**

(standard beam angles, alternative available on request)

