



## OMAR II PANEL (High Efficacy)


LED panels revolutionised lighting in commercial and retail spaces and our market-leading products and options are ready to meet your every application. Our quality reflects our focus on flexibility; a flexibility that ensures the best lighting outcome for every client. Its profile fits seamlessly into any workplace and can be plaster recessed, surface mounted or suspended. The micro-prismatic diffuser delivers low-glare and our LED selection ensures excellent colour rendering to further enhance the comfort and efficiency of the lit space.

**Applications:** Offices, educational, retail stores, supermarkets, hospitals, health services etc.



### PRODUCT FEATURES

- Light output: Up to 3,545Lm
- Efficacy: Up to 177Lm/W
- Ideal for all commercial applications
- Life time: 50,000 hours
- Colour rendering exceeds CRI:80
- Diffuser: Microprismatic
- Beam Angle: 115°
- CCT options: 3000K/4000K
- UGR<19
- Non-waterproof panel: IP50
- Waterproof panel: IP54 (below ceiling) & IP20 (inside ceiling)
- Plaster and surface mount frame accessories available
- Suspension kit available
- Available colour: white
- Dimming options on request
- Flex and plug or direct connection
- Five Year Warranty



Model	Delivered Lumens	System Power	CCT	Beam Angle
PA-OMAR2HE-20	3305Lm	20W	3000K	115°
PA-OMAR2HE-20	3545Lm	20W	4000K	115°

CRI	Material	Voltage	Colour	Dimming Options
>80	PMMA & Aluminium	220-240V, 50Hz	White	Non-Dim/0-10V/DALI

For office locations visit [www.lpalighting.com](http://www.lpalighting.com)



## Accessories

(available on request)



Plaster Frame



Surface Frame



Suspension Kit



Recessed Kit

## Photometrics

(standard beam angles, alternative available on request)

