


AUGUS SR-A590

The Augus is a downlight specifically designed for commercial and high-end hotel projects. Its modular construction and interchangeable components promote a sustainable approach to maintenance and replacements. Its aluminium die-cast housing and heatsink ensure excellent heat dissipation for optimal performance. Available reflector colours are golden, chrome black, silver, black, chrome and white.









Model	Source Power (W)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)				
				Narrow (17°/12°/17°/ 12°/17°)	Medium (23°)	Medium (35°/36°/36°)	Wide (54°/55°/54°)	
SR-A590	12	14	1586	1170	1354	1304	1198	
SR-A590	14	15	1439	1048	-	-	-	
SR-A590	16	19	1586	1562	1823	1759	1622	
SR-A590	22	24	1960	1436	-	-	-	
SR-A590	25	28	1586	2041	2376	2294	2125	
CRI	ССТ	Material	LED Lifetime	Colour	Voltage	Diı	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240\	/ Available	Available on reques	



Accessories

(available on request)

Reflectors available in different colours





Chrome Black



Silver



Black



Chrome




White





Honeycomb Louvre

Photometrics

(standard beam angles, alternative available on request)







AVERAGE BEAM ANGLE (50%):35.8 DEG 0/270,35.5

