


## VISI SR-A767

Visi is an everyday downlight made for professional applications. Once recessed into the ceiling the Visi blends in effortlessly with its narrow trim and provides an anti-glare comfort light. However, trim size is no reflection on performance and Visi provides a full range of illumination levels in both fixed and adjustable design.

Energy efficiency is key and the Visi series are at the top of the performance scale, ensuring significant energy savings over alternative solutions. CCT colours, a honeycomb louvre and dimming options are available on request.







Model	Source Power (W)	System Power (W)	Source Lumen (Lm) _ (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
				Narrow (19°)	Medium (25°)	Medium (38°)	Wide (56°)
SR-A767-H	12	14	1586	1342	1465	1470	1441
SR-A767-J	17	19	2117	1784	1951	1960	1930
SR-A767-K	25	28	2888	2327	2539	2548	2503
CRI	CCT	Material	LED Lifetime	Colour	Voltage	Dimming	
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on reques	



#### Accessories

(available on request)




Honeycomb Louvre

#### **Photometrics**

(standard beam angles, alternative available on request)

## Narrow (19°) at 28W




# -/+180 -150 -120 -120

Medium (25°) at 28W



AVERAGE BEAM ANGLE (50%):24.6 DEG (20/270,24.4

### Medium (38°) at 28W



### Wide (56°) at 28W

