

GENE SS-A047

Gene is a compact luminaire ideal for display areas and small spaces. The flexible design has a horizontal rotation of up to 355° with a tilt up to 30°. Available in a recessed or surface spotlight version.



0	W) System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
Source Power (W)			Narrow (15°)	Narrow (17°)	Narrow (23°)	Wide (47°)
2	3	180	176	171	168	154
ССТ	Material	LED Lifetime	Colour	Voltage	Dimming	
3000K/4000K	Aluminium	50,000 hrs	BK / WH	220-240V	Available on reques	
		2 3 CCT Material	Source Power (w) System Power (w) (CRI>90, 3000K) 2 3 180 CCT Material LED Lifetime	Source Power (W) System Power (W) Source Lumen (Lm) (CRI>90, 3000K) Narrow (15°) 2 3 180 176 CCT Material LED Lifetime Colour	Source Power (W) System Power (W) Source Lumen (Lm) (CRI>90, 3000K) Narrow (15°) Narrow (17°) 2 3 180 176 171 CCT Material LED Lifetime Colour Voltage	Source Power (W) System Power (W) Source Lumen (Lm) (CRI>90, 3000K) Narrow (15°) Narrow (17°) Narrow (23°) 2 3 180 176 171 168 CCT Material LED Lifetime Colour Voltage Dimm



For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.

Accessories


(available on request)




Honeycomb Louvre


Photometrics


(standard beam angles, alternative available on request)





AND ENERGY SOLUTIONS





For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.