

20

210

## DORA ST-C463

The Dora series is a sophisticated LED track light option for accent lighting in retail, hospitality and general display applications. Our market-leading colour rendering, and easy adjustability confirm Dora's excellent suitability for these commercial applications.

All fixtures fit a standard three-circuit track and adjust through 90° vertical plane and 355° horizontal plane. Other options include the choice of CCT colour, a glass lens, an elliptical lens, barn-doors, a honeycomb louvre and a surface mounted canopy.

Also available in surface mount and suspended format.



Source Bower (M)	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K) -	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
Source Power (W)			<b>Narrow</b> (15°/14°)	Narrow (19°)	Medium (41°)	<b>Wide</b> (57°)
17	19	2269	2135	2155	2109	2013
25	27	3107	2943	2973	2912	2788
CCT	Material	LED Lifetime	Colour	Voltage	Dimming	
3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,500 hrs	BK / WH	220-240V	Available on request	
	25 CCT	17 19   25 27   CCT   Material	Source Power (w)     System Power (w)     (CRI>90, 3000K)     -       17     19     2269       25     27     3107       CCT     Material     LED Lifetime       3000K/4000K     Aluminium     L80(12K) > 66,000 hrs	Source Power (W)     System Power (W)     Source Lumen (Lm) (CRI>90, 3000K)     Narrow (15*/14*)       17     19     2269     2135       25     27     3107     2943       CCT     Material     LED Lifetime     Colour       3000K/4000K     Aluminium     L80(12K) > 66,000 hrs     BK / WH	Source Power (W)     System Power (W)     Source Lumen (Lm) (CRI>90, 3000K)     Narrow (15'/14')     Narrow (19')       17     19     2269     2135     2155       25     27     3107     2943     2973       CCT     Material     LED Lifetime     Colour     Voltage       3000K/4000K     Aluminium     L80(12K) > 66,000 hrs     BK / WH     220-240V	Source Power (W)     System Power (W)     Source Lumen (Lm) (CRI>90, 3000K)     Narrow (15'/14')     Narrow (19'')     Medium (41')       17     19     2269     2135     2155     2109       25     27     3107     2943     2973     2912       CCT     Material     LED Lifetime     Colour     Voltage     Dimm       3000K/4000K     Aluminium     L80(12K) > 66,000 hrs     BK / WH     220-240V     Available or




For office locations visit www.lpalighting.com

The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.

## Accessories

(available on request)





**Elliptical Lens** 










Barn Door

**Glass Lens** 


Surface Mounted Canopy


## **Photometrics**

(standard beam angles, alternative available on request)




Medium (41°) at 27W









For office locations visit www.lpalighting.com



The information presented in this document is for information purposes only and does not constitute any obligation on our part. We reserved the right to make technical and design changes at any time and without notice.