




ELVIS DR-A594 (High Efficacy)

Effortlessly accentuate specific areas or features with the Elvis downlight. Its adjustable design can accommodate the most varied applications and boasts an anti-glare device as well as an efficient heatsink ensuring the lifetime of the source. The Elvis series offers fixed, adjustable, IP, trimmed and trimless designs making this series a versatile solution for your lighting needs. This series is designed and manufactured to deliver optimum performance in any environment.



Model	System Power (W)	Source Lumen (Lm) (CRI>90, 3000K)	System Lumen (Lm) / Beam Angle (CRI>90, 3000K)			
			Narrow (16°)	Medium (19°/19°/21°/21°)	Medium (41°/42°/43°/43°)	Wide (56°/56°/55°/55°)
DR-A594-J	14	2016	1570	1534	1528	1532
DR-A594-K	23	3229	2514	2452	2486	2455
DR-A594-L	26	3849	2960	2886	2903	2876
DR-A594-M	36	4672	3802	3732	3707	3700

CRI	CCT	Material	LED Lifetime	Colour	Voltage	Dimming
>90	3000K/4000K	Aluminium	L80(12K) > 66,000 hrs L90 (12K) > 41,000 hrs	BK / WH	220-240V	Available on request



Accessories

(available on request)



Honeycomb Louvre



Elliptical Lens



Glass Lens

Photometrics

(standard beam angles, alternative available on request)

